

Job Name:	
System Reference:	Date:

Indoor Unit: PLA-A36EA7	Outdoor Unit: ☐ PUZ-A36NKA7 ☐ PUZ-A36NKA7-BS
	

INDOOR UNIT FEATURES

- Space-efficient ductless installation
- Equipped with 3D i-see Sensor™ for enhanced comfort and energy efficiency
- Airflow settings for high and low ceiling applications
- Individual vane settings for direct/indirect airflow control or variable airflow patterns
- Knockouts for outside-air intake and branch-duct run
- Filter indicator signal
- Easy-to-clean, washable filter (optional high-efficiency filter available - requires multi-function casement)
- Built-in condensate lift mechanism
- Ideal for retail shops, classrooms, office spaces, conference centers, building lobbies, and more

OUTDOOR UNIT FEATURES

- Variable speed INVERTER-driven compressor
- Suction accumulator pre-charged with refrigerant volume for piping length up to 100 ft (70 ft. for A12/18/24/30)
- 24-hour continuous operation (cooling mode)
- High pressure protection
- Fast restart due to bypass valve make it ideal for equipment cooling applications, such as data centers
- Superior energy and operational efficiency

SPECIFICATIONS: PLA-A36EA7 & PUZ-A36NKA7(-BS)

Model number	Indoor unit		PLA-A36EA7
	Outdoor unit		PUZ-A36NKA7
			PUZ-A36NKA7-BS
Cooling*1	Maximum Capacity	Btu/h	36,000
	Rated Capacity	Btu/h	36,000
	Minimum Capacity	Btu/h	16,000
	Maximum Power Input	W	2,780
	Rated Power Input	W	2,780
	Moisture Removal	Pints/h	4.5
	Sensible Heat Factor		0.86
	Power factor	%	93.7
Heating at 47° F*2	Maximum Capacity	Btu/h	42,000
	Rated Capacity	Btu/h	38,000
	Minimum Capacity	Btu/h	18,000
	Maximum Power Input	W	3,020
	Rated Power Input	W	2,540
	Power factor	%	93.6
Heating at 17° F *3	Maximum Capacity	Btu/h	25,500
	Rated Capacity	Btu/h	22,000
	Maximum Power Input	W	2,550
	Rated Power Input	W	2,490
Efficiency	SEER		21.8
	EER *1		12.9
	HSPF (IV)		10.4
	COP at 47° F *2		4.38
	COP at 17° F *3		2.58
	ENERGY STAR® Certified		Yes
Electrical	Voltage, Phase, Frequency		208 / 230V, 1-phase, 60 Hz
	Guaranteed Voltage Range	V AC	187 - 253
	Voltage: Indoor - Outdoor, S1-S2	V AC	208V / 230
	Voltage: Indoor - Outdoor, S2-S3	V DC	24
	Voltage: Indoor - Remote controller	V DC	12
	Recommended Fuse/Breaker Size	A	30
	Recommended Wire Size (Indoor - Outdoor)	AWG	14
Indoor unit	MCA	A	2.00
	Fan Motor Full Load Amperage	A	0.95

SPECIFICATIONS: PLA-A36EA7 & PUZ-A36NKA7(-BS)

Model number	Indoor unit		PLA-A36EA7
	Outdoor unit		PUZ-A36NKA7
			PUZ-A36NKA7-BS
	Fan Motor Output	W	120
	Airflow Rate, Dry	CFM	670-850-1020-1200
	Airflow Rate, Wet	CFM	630-810-980-1160
	External Static Pressure	in.WG	n/a
	Sound Pressure Level	dB(A)	32-37-41-44
	Drain Pipe Size	In. (mm)	1-1/4 (32)
	Condensate Lift Mechanism, Max. Distance	In. (mm)	33-7/16 (860)
	Heat Exchanger Type		Plate fin coil
	External Finish Color		White Munsell 6.4Y 8.9/0.4
	Unit Dimensions // Grille Dimensions	W: In. (mm)	33-1/16 (840) // 37-13/32 (950)
		D: In. (mm)	33-1/16 (840) // 37-13/32 (950)
		H: In. (mm)	11-3/4 (298) // 1-9/16 (40)
	Package Dimensions // Grille Dimensions	W: In. (mm)	35-9/16 // 39-6/16
		D: In. (mm)	34-5/16 // 38-3/16
		H: In. (mm)	16-9/16 // 4-12/16
	Unit Weight // Grille Weight	Lbs. (kg)	56 (25) // 11 (5)
	Package Weight	Lbs. (kg)	77 (35)
Indoor unit operating temperature range	Cooling Intake Air Temp (Maximum / Minimum)	°F	90 DB, 73 WB / 66 DB, 59 WB
	Heating Intake Air Temp (Maximum / Minimum)	°F	82 DB / 50 DB
Outdoor unit	MCA	A	25
	MOCP	A	31
	Fan Motor Full Load Amperage	A	0.5 + 0.5
	Fan Motor Output	W	74
	Airflow Rate	CFM	3,880
	Refrigerant Control		Electronic Expansion Valve
	Defrost Method		Reverse Cycle
	Heat Exchanger Type		Cross fin
	Sound Pressure Level, Cooling*1	dB(A)	52
	Sound Pressure Level, Heating*2	dB(A)	53
	Compressor Type		Inverter-driven twin rotary
	Compressor Model		MNB33FBRMC-L
	Compressor Rated Load Amps	A	8

SPECIFICATIONS: PLA-A36EA7 & PUZ-A36NKA7(-BS)

Model number	Indoor unit		PLA-A36EA7
	Outdoor unit		PUZ-A36NKA7
			PUZ-A36NKA7-BS
	Compressor Locked Rotor Amps	A	13
	Compressor Oil Type // Charge	oz.	FV50S // 45
	External Finish Color		Ivory Munsell 3Y 7.8/1.1
	Base pan heater		n/a
	Unit Dimensions	W: In. (mm)	1050 [41-5/16]
		D: In. (mm)	330 + 30 [13+1-3/16]
		H: In. (mm)	1338 [52-11/16]
	Package Dimensions	W: In. (mm)	42-15/16
		D: In. (mm)	17-11/16
		H: In. (mm)	56-4/16
	Unit Weight	Lbs. (kg)	214 (97)
	Package Weight	Lbs. (kg)	243 (110)
Outdoor unit operating temperature range	Cooling Intake Air Temp (Maximum / Minimum)	°F	115 DB / 0* DB
	Heating Intake Air Temp (Maximum / Minimum)	°F	70 DB, 59 WB / -4 DB, -4 WB
	Thermal Lock-out / Re-start Temperatures**	°F	-8 / -4 DB
Refrigerant	Type		R410A
	Charge	Lbs, oz	10 lbs, 6 oz
Piping	Gas Pipe Size O.D. (Flared)	In.(mm)	5/8 (15.88)
	Liquid Pipe Size O.D. (Flared)	In.(mm)	3/8 (9.52)
	Maximum Piping Length	Ft. (m)	165 (50)
	Maximum Height Difference	Ft. (m)	100 (30)
	Maximum Number of Bends		15

AHRI Rated Conditions (Rated data is determined at a fixed compressor speed)	*1 Cooling (Indoor // Outdoor)	°F	80°F DB, 67°F WB // 95°F DB, 75°F WB
	*2 Heating at 47°F (Indoor // Outdoor)	°F	70°F DB, 60°F WB // 47°F DB, 43°F WB
	*3 Heating at 17°F (Indoor // Outdoor)	°F	70°F DB, 60°F WB // 17°F DB, 15°F WB
Conditions	*4 Heating at 5°F (Indoor // Outdoor)	°F	70°F DB, 60°F WB // -4°F DB, -5°F WB
Notes			
*Wind baffles required to operate below 23°F DB in cooling mode. PUZ with wind baffle: 0°F - 115°F.			
**System cuts out in heating mode to avoid thermistor error and automatically restarts at these temperatures			

SPECIFICATIONS: PLA-A36EA7 & PUZ-A36NKA7(-BS)

SEACOAST PROTECTION

External Outer Panel: Phosphate coating + Acrylic-Enamel coating

Fan Motor Support: Epoxy resin coating (at edge face)

Separator Assembly; Valve Bed: Epoxy resin coating (at edge face)

“Blue Fin” treatment is an anti-corrosion treatment that is applied to the condenser coil to protect it against airborne contaminants.

Notes:

ACCESSORIES: PLA-A36EA7 & PUZ-A36NKA7(-BS)

PLA-A36EA7	
High Efficiency (MERV 10) Filter Element (Requires PAC-SJ41TM-E Multi-Function Casement)	□ PAC-SH59KF-E
Grille with 3D i-see Sensor™	□ PLP-40EAEU
Air outlet shutter Plate	□ PAC-SJ37SP-E
Multi-functional Casement	□ PAC-SJ41TM-E
Flange for fresh-air Intake	□ PAC-SH65OF-E
3-Pole Disconnect Switch (30A/600V/UL) [fits 2" X 4" utility box]	□ TAZ-MS303
Drain Pan Level Sensor (Control for indoor unit shut off to prevent drain pan overflow)	□ DPLS2
Advanced Blue Diamond Mini-Condensation pump w/ Reservoir & Sensor (110V)	□ X87-711 - 110
Advanced Blue Diamond Mini-Condensation pump w/ Reservoir & Sensor (208/230V)	□ X87-721 - 208/230
Extension Cord for Blue Diamond Pump	□ C13-103
MegaBlue Blue Diamond Condensate Pump (110-230V)	□ X87-835
Remote Sensor (extensible)	□ PAC-SE41TS-E
Connector for CN32 (remote on/off)	□ PAC-SE55RA-E
Remote Operation Adapter (with wire terminals for remote on/off and operation status/error)	□ PAC-SF40RM-E*1
External fan / Heater control relay adapter	□ CN24RELAY-KIT-CM3
Backlit, wall-mounted, wireless	□ MHK1
Wireless Remote Controller	□ MRCH1
Wireless Receiver	□ MFH1
Portable Central Controller	□ MCCH1
Outside Air Sensor	□ MOS1
Wireless adapter	□ PAC-USWHS002-WF-1
BACnet® and Modbus Interface	□ PAC-UKPRC001-CN-1
Wall-mounted, Wired	□ PAC-YT53CRAU-J
Wired remote controller	□ PAR-32MAA-J
T-STAT Interface	□ PAC-US444CN-1
Wired remote controller	□ PAR-32MAA
Signal Receiver	□ PAR-SR3LA-E
Simple remote controller	□ PAC-YT53CRAU
Wireless Remote Controller	□ PAR-FL32MA-E
Wire for Remote ON/OFF with CN32 connector	□ PAC-715AD
Lockdown Bracket for wireless, hand-held, remote controllers	□ RCMKP1CB

*1 Unable to use with wireless remote controller

ACCESSORIES: PLA-A36EA7 & PUZ-A36NKA7(-BS)

PUZ-A36NKA7(-BS)	
Twinning Distribution Pipe (50:50)	□ MSDD-50TR-E
Air Outlet Guide (two pieces are required)	□ PAC-SH96SG-E
Front Wind Baffle (two pieces are required)	□ WB-PA3
Drain socket	□ PAC-SG61DS-E
Centralized Drain Pan	□ PAC-SH97DP-E
M-NET Converter	□ PAC-SF83MA-E
Control/Service Tool	□ PAC-SK52ST
Wall mounting bracket (Powder-coated Steel)	□ QCWB2000M-1
Wall mounting bracket (316 Series Stainless Steel)	□ QCWBSS
M-NET control adapter for Building Management System	□ PAC-SF83MA-E
Outdoor Unit Mounting Pad 24" x 42" x 3"	□ ULTRILITE2
Outdoor Unit 3-1/4 inch Mounting Base - Pair (Plastic)	□ DSD-400N
MiniSplit Mounting Stand-Dual Fan models - 12"	□ QSMS1202M
MiniSplit Mounting Stand-Dual Fan models - 18"	□ QSMS1802M
MiniSplit Mounting Stand-Dual Fan models - 24"	□ QSMS2402M
3/8 x 5/8 x 10' / 1/2" Lineset (Twin-Tube Insulation)	□ MPLS385812T-10
3/8 x 5/8 x 15' / 1/2" Lineset (Twin-Tube Insulation)	□ MPLS385812T-15
3/8 x 5/8 x 30' / 1/2" Lineset (Twin-Tube Insulation)	□ MPLS385812T-30
3/8 x 5/8 x 50' / 1/2" Lineset (Twin-Tube Insulation)	□ MPLS385812T-50
3/8 x 5/8 x 65' / 1/2" Lineset (Twin-Tube Insulation)	□ MPLS385812T-65
3/8 x 5/8 x 100' / 1/2" Lineset (Twin-Tube Insulation)	□ MPLS385812T-100

PLA-A36EA7

Unit: inch (mm)



